

Custom signage is available to meet your requirements.

PermaLight photoluminescent signage charges in the presence of incandescent, fluorescent or natural light and gives off light for up to 10 hours in total darkness. (Note: Sodium Vapor light source will not provide adequate charging.)

For low-location egress routing, bottom of signage or marker should be mounted not less than 6" or more than 8" above the floor.

For other Johnsonite Safe-T-First products, see our Interior Design Flooring Solutions and Marking Indicator literature and our complete Safe-T-First brochure.

Virtually any size, shape, color or graphic style available. Signs comply with ADA requirements of 30/70 background to foreground contrast ratio with photoluminescent background.

Signage available:

- In surface and sub-surface silk screening
- With raised characters and letters
- In matte or gloss finish
- In standard yellow or white PermaLight
- In various typefaces (fonts)
- With or without Braille
- With or without border frames



Johnsonite®
Flooring Solutions to Integrate Design & Life-Safety

A Division of Duramax, Inc.
16910 Munn Road, Chagrin Falls, Ohio 44023
(800) 899-8916 Fax (440) 543-8920
In Canada: 560 Weber Street N., Waterloo, Ontario N2L 5C6
(800) 899-8916 Fax (519) 747-9155
www.johnsonite.com
e-mail: info@johnsonite.com

© 1999 Johnsonite, Div. of Duramax, Inc.
Printed in the USA 95000-666 3/99 306012

Specifier Information Services

Architects, designers, facility managers or end-users may call 1-800-899-8916, fax to 1-440-543-8920 or e-mail to info@safe-t-first.com for:

- Our complete Safe-T-First brochure, Interior Design Flooring Solutions and Marking Indicator Safety Solutions literature
- Safe-T-First technical advisor
- Architectural specifications and testing information
- Safe-T-First CD-ROM presentation
- Product samples

Visit our educational Web site at www.safe-t-first.com.

Safe-T-First Web site contains technical information, complete photoluminescent reference library and product information. These materials may also be downloaded for your convenience.

Complies with Americans with Disabilities Act regulations.

Meets photoluminescent escape routing standards in D.I.N. 67510.

Meets building code standards from American National Standard Institute.

Member National Safety Council

Note: Photographs may not duplicate exact color of PermaLight material.